



The Workhorse laminator

The Workhorse is our recommended laminator because it is just that... a Workhorse.

A 50 yd. roll of material will laminate perfectly straight when set up properly. Changing materials and laminates is very quick and easy.

The Workhorse Laminate

Dependable and versatile for Hot or Cold laminates up to 25" wide.



DESIGN

Designs & logos can be imported from many programs such as Adobe® Illustrator® as well as PDF files. Jobs can be created using Omega's powerful design tools which includes variable data & barcode tools.



PRINT

The Gerber Edge FX uses an efficient, environmentally friendly thermal printing process that produces durable dry prints with no waste, odor, or harmful emissions.



With a top speed of 25 FPM, a 50 yd. roll of labels can be done in 6 minutes. The Workhorse comes on a stand and has optional casters.

It also comes with simple slitting knives for rough slitting.

This industrial series laminator is ideal for hot and cold laminating, both in sheet and roll form...



Features & Specifications

- Intelligent heat controllers display both the set temperature and the actual temperature. The micro-processor in the control quickly learns to anticipate the heat demand of each job and keeps the actual temperature within a few degrees of the set temperature.
- Upper and lower rollers are mechanically driven. This prevents roll curling. Other less expensive laminators that cut corners on design may only drive the upper or lower rollers, which creates friction on one side only. This can make the material curl as it is pulled through the laminator.
- Laminating and pull rollers are covered with quality silicone rubber for superior release quality, higher lamination quality and easier cleaning. The laminating rollers and pull rollers are interchangeable.
- Removeable Heat Shoes are teflon coated to reduce film abrasion and are easily unplugged and removed to clean or replace the rollers.
- Dual tension knobs (clutches) for each supply roll mandrel are easy to use and provide as little or as much tension as needed to keep work wrinkle-free.
- Easy access controls are conveniently located and grouped for effective operation.
- A safety guard is built into the sheet feed tray to help insure it will always be in place when laminating sheets.

SPECIFICATIONS

Laminating width:	25"
Dimensions:	36L 21H 30D
Weight/shipping wt.:	185/285 lbs
Speed:	0-25 fpm
Electrical:	220 V
	3500 watts, 20 amps
Recommended film up to	20 mil
Max. laminating thickness	1/2"
Max. film roll diameter	8" (14" Opt)
Lam. roll diameter	1.5"
Supply role core size	3" (2 1/4" opt)
Motor	1/4 HP DC

LAMINATE

The laminator component of the system gives you the versatility to include specified adhesives and coverings that add texture, high-gloss or protection to your product markings or control panels. Lamination will also add abrasion resistance and more durability to labels.

CUT

The enVision 375 is a tabletop, sprocket-fed plotter that will digitally die cut any shape with the push of a button. Simply set the depth of the cut(s) and send the job to the plotter.



Our No Stress Rule

We know that any investment carries some level of risk.

Our goal is for you to feel completely comfortable embracing the Gerber Edge FX® for your marking needs. We believe in the technology and have created no obligation rent programs, rent-to-buy, and leasing options.

We are successful only when you are successful.



GRAPHIC
Marking Systems

28457 N. Ballard Dr., Suite A1, Lake Forest, IL. 60045
1-800-232-8018 www.GraphicMS.com